


TECHNICAL DATA SHEET

K23 LINEN OPTIC

K23 LINEN OPTIC is a bioriented polypropylene film, with a special linen effect coating on one side. The other side is corona treated.

This film complies with EN-71 (declaration on request). This film is not suitable for direct contact with food.



TYPICAL TECHNICAL FEATURES ⁽¹⁾

PHYSICAL PROPERTIES	METHOD	UNIT	VALUE <i>code 137/23</i>
Thickness	Internal	µm	23 ± 1,15
Grammage	Internal	g/m ²	14,4
Surface tension	coated side Internal	dyne/cm	≥ 40

STORAGE

Store the material in a dry location (preferably with RH ≤ 50%) at a constant temperature between 10°C and 30°C. Do not leave it exposed to direct sunlight or atmospheric agents. Partially used reels have to be repacked as originally supplied.

WARRANTY

Material processability is guaranteed up to 6 months since shipment date, as long as it is stored correctly. It is recommended to condition the material at room temperature at least 24 hours before its use.

DISCLAIMERS

ULTRALEN FILM GmbH gives no warranty, expressed or implied, as to the suitability of the material for a specific application or characteristic use. An industrial homologation test of the material in actual conditions of purpose is always needed in order to verify its suitability for the specific application or characteristic use. Before using the material, it is advisable to check the compatibility of the inks and adhesives to be purposed with the type and level of its treatment.

⁽¹⁾ The information and data contained herein are to be used only as a guideline; therefore, ULTRALEN FILM GmbH doesn't offer any guarantee on their absolute truthfulness and doesn't accept any liability arising out of their use.